

PRODUCT INFORMATION

NAVIGREASE EP 2

Description

NAVIGREASE EP 2 is a lithium thickened multi-purpose lubricating grease.

Application

NAVIGREASE EP 2 is a high quality multi-purpose grease for marine applications. The grease is suitable for a wide range of plain and rolling bearings.

Features/Advantages and Benefits

- Good load carrying capacity
- Effective protection against corrosion
- Suitable for various applications within given temperature limits
- Meets DIN 51825 specification KP2K-30

Typical Characteristics

Characteristic	Method	Unit	
Thickener	-	-	Lithium
Color	-	-	Brown
NLGI-Grade	ASTM D 217	-	2
Dropping Point	IP 396	°C	195
Base Oil Viscosity at 40°C	ISO 12058	mm ² /s	200
Temperature Operating Range	-	°C	-30...130
Copper Corrosion 24h/ 100°C	ASTM D 4048	-	1a

MARINE IN ALL WE DO!

Health and Safety

The Safety Data Sheet is available on request and describes the product from the points of view of safety in use, handling and transport. The product is not classified as dangerous according to the provisions of the Regulation 1907/2006, and of the Directives D67/548/CEE and 1999/45/CE, respectively. Under normal use conditions, this product does not pose significant risks for the health. Repeated exposure may cause skin drying or cracking. Immediately wash the area that came in contact with the product with plenty of water and soap. Remove contaminated clothes.

Handling and Packaging

The compatibility and miscibility with comparable products from other suppliers with same thickener and similar base oils have been tested successfully. Generally grease made of e.g. lithium thickener and mineral oil can be mixed with grease based on the same type of thickener and mineral oil. Also, greases with different thickeners e.g. calcium complex and lithium complex greases, are miscible with each other. However, these are only general guidelines and to achieve full scale benefits of product performance the mixing of lubricants should be avoided or kept to a minimum. Hence, we recommend replacing of old grease fillings where easily achievable.

Re-lubrication shall be done when the condition of the lubricant is still suitable for continued service. The required quantity varies with bearing type, speed, temperature range and other related factors. Details shall be obtained from the manufacturer's manual.

The grease collar outside of bearings prevents ingress of dirt and water. When refilling the product ingress of dust and water must be avoided. It is possible to renew the entire grease fill if the system is equipped with grease nipples and exit holes.

Pails should be stored in their unopened original packaging, in an upright position and in a dry place. Always avoid water contamination.

The product is available in pails. The pack size may vary in different regions or countries.

Further Information

For further information about LUKOIL Marine Lubricants please contact any representative of LUKOIL Marine Lubricants or visit our web site www.lukoilmarine.com.

LUKOIL Marine Lubricants Ltd.
June 2011